



Flexible coated conduit CP-CDT-SLT-1/4-10M


- Halogen-free
- 1/4" flexible coated conduit

1/4" flexible coated conduit 10 m

Function

The flexible coated conduit is used in conjunction with a suitable sensor adapter and a suitable cable gland to form a cable protection system for sensors. The purpose of this system is to protect the sensor wiring in harsh environments.

Dimensions



Technical Data

Ambient conditions	
Ambient temperature	- 55 ... 105 °C (131 ... 221 °F)
Mechanical specifications	
Length	L 10 m
Bending radius	static 40 mm dynamic 50 mm
Degree of protection	IP67
Mech. capacity	
Impact resistance	Class 4, heavy (6 J) , according to EN-IEC 61386
Pressure resistance	Class 4, heavy (1250 N) , according to EN-IEC 61386
Tensile strength	Class 4, heavy (1000 N) , according to EN-IEC 61386
Material	galvanized steel cable , PUR (halogen-free) jacketed

Release date: 2020-06-30 Date of issue: 2020-06-30 Filename: 308744_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com






Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

PF PEPPERL+FUCHS

Technical Data

Mass	1550 g
General information	
Supplementary information	observe mounting instructions

Matching system components

	CP-ADP-SLT-1/4-M8 5pcs	Sensor adapter for M8 sensors and 1/4" flexible coated conduit
	CP-ADP-SLT-1/4-M12 5pcs	Sensor adapter for M12 sensors and 1/4" flexible coated conduit
	CP-ADP-SLT-1/4-M14 5pcs	Sensor adapter for M14 sensors and 1/4" flexible coated conduit
	CP-CGL-SLT-1/4-M12 5pcs	Cable gland M12 for cable diameter 1 ... 5.2 mm and 1/4" flexible coated conduit
	CP-CGL-SLT-1/4-M16 5pcs	Cable gland M16 for cable diameter 1 ... 5.2 mm and 1/4" flexible coated conduit