

Temperature sensor USI-TEMP-1,5M-V312




- Compact design
- Universal orientation
- Mounting holes for simple installation

Temperature sensor exclusively for the USi-safety evaluation unit



Dimensions



Technical Data

General specifications	
Type	Temperature sensor
Electrical specifications	
Measuring resistor	NTC resistor 4.7 k Ω at 25 °C B value (B _{25/100}) = 3980 K \pm 3%
Ambient conditions	
Ambient temperature	movable cable: -25 ... 80 °C (-13 ... 176 °F) fixed cable: -40 ... 80 °C (-40 ... 176 °F)
Storage temperature	-40 ... 85 °C (-40 ... 185 °F)
Mechanical specifications	
Connection type	fixed cable with plug
Housing diameter	6.5 mm
Degree of protection	IP67
Material	
Housing	TPU
Connector	
Threading	M8 x 1
Number of pins	6

Release date: 2023-08-04 Date of issue: 2023-08-04 Filename: 70131328_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

 PEPPERL+FUCHS

Technical Data

Material		PUR
Cable		
Cable diameter		5 mm
Bending radius		fixed cable: > 5 x cable diameter movable cable: > 10 x cable diameter
Material		PUR
Color		black
Length	L	1.5 m ± max. 40 mm
Mass		22 g

Commissioning

This component is only intended for use in conjunction with the ultrasonic sensor system USi-safety. Further details, mounting and commissioning instructions for the safe ultrasonic sensor system USi-safety can be found in the original instructions on the respective product page at www.pepperl-fuchs.com.

Matching System Components

	USI-F262-2E5-V19-S2D3	Evaluation unit exclusively for the ultrasonic sensor system USi-safety
---	------------------------------	---