

# Bulk Raw Cable

## CBL-PVC-GY-04x034-100M



Cable, PVC/PVC, 4-core grey



### Dimensions



### Technical Data

<b>Electrical specifications</b>		
Operating voltage	$U_B$	max. 300 V AC/DC
<b>Conformity</b>		
Flammability		IEC 60332-2-2
<b>Ambient conditions</b>		
Ambient temperature		
Cable, fixed		-25 ... 70 °C (-13 ... 158 °F)
Cable, flexing		-25 ... 80 °C (-13 ... 176 °F)
Pollution degree		3
<b>Mechanical specifications</b>		
Cable		according to IEC/EN 60228 (DIN VDE 0295) class 5
Sheath diameter		4.8 mm ± 0.2 mm
Bending radius		> 10 x cable diameter, moving
Sheath stripping force		max. 80 N / 300 mm
Sheath color		grey (similar to RAL 7001)
Number of cores		4
Core cross section		0.34 mm <sup>2</sup>

Release date: 2023-02-20 Date of issue: 2023-02-20 Filename: 227000\_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group  
www.pepperl-fuchs.com

USA: +1 330 486 0001  
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111  
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091  
fa-info@sg.pepperl-fuchs.com

PEPPERL+FUCHS












## Technical Data

Cores color		Core 1: brown Core 2: white Core 3: blue Core 4: black
Core construction		19 x 0.15 mm Ø
Length	L	100 m
Cable code		Li Y YM 4 x 0,34
<b>Material</b>		
Cable		
Sheathing		PVC
Core insulation		PVC
Flammability		flame-resistant

## Connection Assignment

————— ······ —————	BN
————— ······ —————	WH
————— ······ —————	BU
————— ······ —————	BK

## Accessories

	<b>V1-G-Q3</b>	Field-attachable female QUICKON-ONE connector
	<b>V1-WV2A</b>	Female connector, field-attachable
	<b>V1S-G-Q3</b>	Field-attachable male QUICKON-ONE connector
	<b>V1-G-Q2</b>	Field-attachable female QUICKON-ONE connector
	<b>V1S-G-Q2</b>	Field-attachable male QUICKON-ONE connector
	<b>V1-G-BK</b>	Female connector M12 straight A-coded 4-pin, for cable diameter 4 - 6 mm, field-attachable
	<b>V1-W-BK</b>	Female connector M12 angled A-coded 4-pin, for cable diameter 4 - 6 mm, field-attachable
	<b>V1S-G-BK</b>	Male connector M12 straight A-coded 4-pin, for cable diameter 4 - 6 mm, field-attachable
	<b>V1S-W-BK</b>	Male connector M12 angled A-coded 4-pin, for cable diameter 4 - 6 mm, field-attachable
	<b>V31-WM-MQ</b>	Female cordset single-ended, M8, 4-pin, field attachable
	<b>V31-WM</b>	Female cordset single-ended, M8, 4-pin, field attachable









Release date: 2023-02-20 Date of issue: 2023-02-20 Filename: 227000\_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group  
www.pepperl-fuchs.comUSA: +1 330 486 0001  
fa-info@us.pepperl-fuchs.comGermany: +49 621 776 1111  
fa-info@de.pepperl-fuchs.comSingapore: +65 6779 9091  
fa-info@sg.pepperl-fuchs.com

**PEPPERL+FUCHS**

## Accessories

	<b>V31S-WM</b>	Field-attachable male connector, M8, 4-pin
	<b>V1S-GV4A</b>	Male connector, field-attachable
	<b>V1-W-SC</b>	Female connector M12 angled A-coded 4-pin, for cable diameter 4 - 8 mm, field-attachable, cage spring connection
	<b>V1S-W-SC</b>	Male connector M12 angled A-coded 4-pin, for cable diameter 4 - 8 mm, field-attachable, cage spring connection
	<b>V31-GM-Q4</b>	Female cordset single-ended, M8, 4-pin, field attachable
	<b>V31S-GM-Q4</b>	Field-attachable male connector, M8, 4-pin
	<b>V31S-GM</b>	Male connector, field-attachable
	<b>V31-GM</b>	Female cordset single-ended, M8, 4-pin, field attachable