



Model Number

VAZ-TUNER

Active bus terminal resistor

Features

- Cable extension to up to 300 m per segment possible
- Simple commissioning by means of rotary selector
- Optimized bus terminator parameters

Function

By connecting each individual AS-Interface network with a VAZ-TUNER consisting of an ohmic, capacitive and inductive part, the signal quality can be improved and the AS-Interface voltage monitored.

During a teach-in phase, the VAZ-TUNER analyses the number of AS-Interface telegram repetitions, i. e., the AS-Interface telegrams that have not been detected and adjusts its impedance automatically such that their number is minimised. This way, optimum parameters are achieved for the respective network. Due to this adjustment, the 100 m limit can be extended to up to 300 m for the optimised network.

By means of three LEDs, the quality of the AS-Interface communication is permanently indicated. Errors are stored and can be acknowledged via a button. The user can see at a glance whether the quality of the AS-Interface installation is ok.

Technical data

General specifications

AS-Interface specification	V3.0
----------------------------	------

Indicators/operating means

LED ERROR	AS-Interface error; LED red
LED WARNING	AS-Interface warning; LED yellow
LED GREEN	AS-Interface OK; LED green
LED POWER	AS-Interface voltage; LED green

Input

Supply	from AS-Interface
Input current	≤ 60 mA

Directive conformity

Electromagnetic compatibility	
Directive 2014/30/EU	EN 62026-2:2013 EN 61000-6-2:2005, EN 61000-6-4:2007

Standard conformity

Electromagnetic compatibility	EN 61000-6-2:2005 EN 61000-6-4:2007
Degree of protection	EN 60529:2000
AS-Interface	EN 62026-2:2013

Ambient conditions

Ambient temperature	0 ... 55 °C (32 ... 131 °F)
Storage temperature	-25 ... 70 °C (-13 ... 158 °F)

Mechanical specifications

Degree of protection	IP65
Connection	cable piercing method or terminal compartment flat cable or standard round cable

Note	Purpose: improvement of signal quality and voltage monitoring operation on the most remote AS-Interface strand (up to 300 m).
------	---