




Female cordset V112-G-BK2M-PUR

- Suitable for drag chains and abrasion resistant
- Resistant to microbes and hydrolysis
- Halogen-free
- Immunity to vibration, with mechanical latching
- Knurled nut suitable for tool assembly

Female cordset single-ended M12 straight A-coded, 12-pin, PUR cable black



Dimensions



Technical Data

General specifications

Connector 1			
Connection		socket	
Construction type		M12	
Style		straight	
Locking		screw connection	
Number of pins		12	
Coding		A-coded	
Connector 2			
Connection		cable end	

Electrical specifications

Operating voltage	U_B	30 V
Operating current	I_B	1.5 A
Surge protection		category II

Conformity

Degree of protection	EN 60529		
Plug connection	connector M12 x 1 : IEC 61076-2-101		

Release date: 2021-02-10 Date of issue: 2021-02-10 Filename: 299848_eng.pdf


Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Technical Data

Microbial resistance	EN 50396 / DIN VDE 0282-10	
Hydrolysis resistance	EN 50396 / DIN VDE 0282-10	
Oil resistance	DIN EN 60811-2-1 / DIN VDE 0472 T.803, test type B	
Ambient conditions		
Ambient temperature		
Plug connector	-25 ... 85 °C (-13 ... 185 °F)	
Cable, fixed	-40 ... 80 °C (-40 ... 176 °F)	
Cable, flexing	-5 ... 80 °C (23 ... 176 °F)	
Pollution degree	3	
Mechanical specifications		
Plug connector		
Tightening torque	0.4 Nm	
Tool installation	straight knurling	
Mating cycles	min. 100	
Degree of protection	IP65/IP67/IP68	
Cable		
Sheath diameter	7.2 mm	
Bending radius	54 mm	
Sheath color	black (similar to RAL 9005)	
Number of cores	12	
Core cross-section	0.14 mm ²	
Cores color	Core 1: brown Core 2: blue Core 3: white Core 4: green Core 5: pink Core 6: yellow Core 7: black Core 8: grey Core 9: red Core 10: violet Core 11: grey/pink Core 12: red/blue	
Core construction	18 x 0.1 mm	
Length	L	2 m
Drag chain suitability		
Drag chain cycles	min. 4000000	
Motion velocity	max. 3 m/s	
Traverse distance	10 m	
Acceleration	max. 10 m/s ²	
Material		
Halogen-free	yes	
Plug connector		
Screw connection	Zinc diecast, nickel-plated	
Body	TPU, black	
Seal	NBR	
Contact surface	Ni/Au	
Flammability	V-0	
Cable		
Sheathing	PUR	
Core insulation	PP	

Release date: 2021-02-10 Date of issue: 2021-02-10 Filename: 299848_eng.pdf

Connection Assignment



1)	-----	BN
2)	-----	BU
3)	-----	WH
4)	-----	GN
5)	-----	PK
6)	-----	YE
7)	-----	BK
8)	-----	GY
9)	-----	RD
10)	-----	VT
11)	-----	GYPK
12)	-----	RDBU

Release date: 2021-02-10 Date of issue: 2021-02-10 Filename: 299848_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com