



SIMATIC HMI, KTP700 Basic, Basic Panel, Key/touch operation, 7" TFT display, 65536 colors, PROFINET interface, configurable from WinCC Basic V13/ STEP 7 Basic V13, contains open-source software, which is provided free of charge see enclosed CD

| General information   |  |
|---|--|
| Product type designation  | KTP700 Basic color PN                    |
| Display   |  |
| Design of display   | TFT widescreen display, LED backlighting |
| Screen diagonal   | 7 in                                     |
| Display width   | 154.1 mm                                 |
| Display height  | 85.9 mm                                  |
| Number of colors  | 65 536                                   |
| Resolution (pixels)   |  |
| • Horizontal image resolution   | 800 pixel                                |
| • Vertical image resolution   | 480 pixel                                |
| Backlighting  |  |
| • MTBF backlighting (at 25 °C)  | 20 000 h                                 |
| • Backlight dimmable  | Yes                                      |
| Control elements  |  |
| Keyboard fonts  |  |
| • Function keys   |  |
| — Number of function keys   | 8  |
| — Number of function keys with LEDs                                   | 0  |
| • Keys with LED   | No                                       |
| • System keys   | No                                       |
| • Numeric keyboard  | Yes; Onscreen keyboard                   |
| • alphanumeric keyboard   | Yes; Onscreen keyboard                   |
| Touch operation   |  |
| • Design as touch screen  | Yes; Analog-resistive                    |
| Installation type/mounting  |  |
| Mounting position   | vertical                                 |
| Wall mounting/direct mounting   | No                                       |
| Mounting in portrait format possible                                  | Yes                                      |
| Mounting in landscape format possible                                 | Yes                                      |
| maximum permissible angle of inclination without external ventilation | 35°                                      |
| Supply voltage  |  |
| Type of supply voltage  | DC                                       |
| Rated value (DC)  | 24 V                                     |
| permissible range, lower limit (DC)                                   | 19.2 V                                   |
| permissible range, upper limit (DC)                                   | 28.8 V                                   |
| Input current   |  |
| Current consumption (rated value)                                     | 230 mA                                   |
| Starting current inrush I <sup>2</sup> t                              | 0.2 A <sup>2</sup> ·s                    |

| Power  |   |
|--|---|
| Active power input, typ.                         | 5.5 W                                   |
| Processor  |   |
| Processor type                                   | ARM                                     |
| Memory   |   |
| Flash  | Yes                                     |
| RAM  | Yes                                     |
| Memory available for user data                   | 10 Mbyte                                |
| Type of output                                   |   |
| Acoustics  |   |
| • Buzzer   | Yes                                     |
| • Speaker  | No                                      |
| Time of day                                      |   |
| Clock  |   |
| • Hardware clock (real-time)                     | Yes                                     |
| • Software clock                                 | Yes                                     |
| • retentive                                      | Yes; Back-up duration typically 6 weeks |
| • synchronizable                                 | Yes                                     |
| Interfaces                                       |   |
| Number of industrial Ethernet interfaces         | 1                                       |
| Number of RS 485 interfaces                      | 0                                       |
| Number of RS 422 interfaces                      | 0                                       |
| Number of RS 232 interfaces                      | 0                                       |
| Number of USB interfaces                         | 1; Up to 16 GB                          |
| Number of 20 mA interfaces (TTY)                 | 0                                       |
| Number of parallel interfaces                    | 0                                       |
| Number of other interfaces                       | 0                                       |
| Number of SD card slots                          | 0                                       |
| With software interfaces                         | No                                      |
| Industrial Ethernet                              |   |
| • Industrial Ethernet status LED                 | 2                                       |
| Protocols  |   |
| PROFINET   | Yes                                     |
| Supports protocol for PROFINET IO                | No                                      |
| IRT  | No                                      |
| PROFIBUS   | No                                      |
| EtherNet/IP                                      | Yes                                     |
| MPI  | No                                      |
| Protocols (Ethernet)                             |   |
| • TCP/IP   | Yes                                     |
| • DHCP   | Yes                                     |
| • SNMP   | Yes                                     |
| • DCP  | Yes                                     |
| • LLDP   | Yes                                     |
| WEB characteristics                              |   |
| • HTTP   | No                                      |
| • HTML   | No                                      |
| Redundancy mode                                  |   |
| Media redundancy                                 |   |
| — MRP  | No                                      |
| Further protocols                                |   |
| • CAN  | No                                      |
| • MODBUS   | Yes; Modicon (MODBUS TCP/IP)            |
| Interrupts/diagnostics/status information        |   |
| Diagnoses  |   |
| • Diagnostic information readable                | No                                      |
| EMC  |   |
| Emission of radio interference acc. to EN 55 011 |   |
| • Limit class A, for use in industrial areas     | Yes                                     |
| • Limit class B, for use in residential areas    | No                                      |

| Degree and class of protection                     |  |
|--|--|
| IP (at the front)                                  | IP65   |
| IP (rear)  | IP20   |
| NEMA (front)                                       |  |
| • Enclosure Type 4 at the front                    | Yes  |
| • Enclosure Type 4x at the front                   | Yes  |
| Standards, approvals, certificates                 |  |
| CE mark  | Yes  |
| cULus  | Yes  |
| RCM (formerly C-TICK)                              | Yes  |
| KC approval  | Yes  |
| Use in hazardous areas                             |  |
| • ATEX Zone 2                                      | No   |
| • ATEX Zone 22                                     | No   |
| • IECEx Zone 2                                     | No   |
| • IECEx Zone 22                                    | No   |
| • cULus Class I Zone 1                             | No   |
| • cULus Class I Zone 2, Division 2                 | No   |
| • FM Class I Division 2                            | No   |
| Marine approval                                    |  |
| • Germanischer Lloyd (GL)                          | Yes  |
| • American Bureau of Shipping (ABS)                | Yes  |
| • Bureau Veritas (BV)                              | Yes  |
| • Det Norske Veritas (DNV)                         | Yes  |
| • Lloyds Register of Shipping (LRS)                | Yes  |
| • Nippon Kaiji Kyokai (Class NK)                   | Yes  |
| • Polski Rejestr Statkow (PRS)                     | No   |
| • Chinese Classification Society (CCS)             | No   |
| Ambient conditions                                 |  |
| Ambient temperature during operation               |  |
| Operation (vertical installation)                  |  |
| — For vertical installation, min.                  | 0 °C   |
| — For vertical installation, max.                  | 50 °C  |
| Operation (max. tilt angle)                        |  |
| — At maximum tilt angle, min.                      | 0 °C   |
| — At maximum tilt angle, max.                      | 40 °C  |
| Operation (vertical installation, portrait format) |  |
| — For vertical installation, min.                  | 0 °C   |
| — For vertical installation, max.                  | 40 °C  |
| Operation (max. tilt angle, portrait format)       |  |
| — At maximum tilt angle, min.                      | 0 °C   |
| — At maximum tilt angle, max.                      | 35 °C  |
| Ambient temperature during storage/transportation  |  |
| • min.   | -20 °C                                       |
| • max.   | 60 °C  |
| Relative humidity                                  |  |
| • Operation, max.                                  | 90 %; no condensation                        |
| Operating systems                                  |  |
| proprietary  | Yes  |
| pre-installed operating system                     |  |
| • Windows CE                                       | No   |
| configuration / header                             |  |
| Message indicator                                  | Yes  |
| Alarm system (incl. buffer and acknowledgment)     | Yes  |
| Process value display (output)                     | Yes  |
| Process value default (input) possible             | Yes  |
| Recipe management                                  | Yes  |
| Configuration software                             |  |
| • STEP 7 Basic (TIA Portal)                        | Yes; via integrated WinCC Basic (TIA Portal) |
| • STEP 7 Professional (TIA Portal)                 | Yes; via integrated WinCC Basic (TIA Portal) |

|                                   |     |
|-----------------------------------|-----|
| • WinCC flexible Compact          | No  |
| • WinCC flexible Standard         | No  |
| • WinCC flexible Advanced         | No  |
| • WinCC Basic (TIA Portal)        | Yes |
| • WinCC Comfort (TIA Portal)      | Yes |
| • WinCC Advanced (TIA Portal)     | Yes |
| • WinCC Professional (TIA Portal) | Yes |

## Languages

### Online languages

|                                      |    |
|--------------------------------------|----|
| • Number of online/runtime languages | 10 |
|--------------------------------------|----|

### Project languages

|                         |    |
|-------------------------|----|
| • Languages per project | 32 |
|-------------------------|----|

## Functionality under WinCC (TIA Portal)

### Libraries

Yes

### Applications/options

|                             |  |
|-----------------------------|--|
| • Web browser               | Yes  |
| • SIMATIC WinCC Sm@rtServer | Yes; Available with WinCC (TIA Portal) V14 or higher |

### Number of Visual Basic Scripts

No

### Task planner

|                   |     |
|-------------------|-----|
| • time-controlled | No  |
| • task-controlled | Yes |

### Help system

|                                      |     |
|--------------------------------------|-----|
| • Number of characters per info text | 500 |
|--------------------------------------|-----|

### Message system

|   |   |
|---|---|
| • Number of alarm classes                                   | 32  |
| • Bit messages  |   |
| — Number of bit messages                                    | 1 000   |
| • Analog messages   |   |
| — Number of analog messages                                 | 25  |
| • S7 alarm number procedure                                 | No  |
| • System messages HMI                                       | Yes   |
| • System event, more (SIMATIC S7, SINUMERIK, SIMOTION, ...) | Yes; System message buffer of the SIMATIC S7-1200 and S7-1500 |
| • Number of characters per message                          | 80  |
| • Number of process values per message                      | 8   |
| • Acknowledgment groups                                     | Yes   |
| • Message indicator   | Yes   |
| • Message buffer  |   |
| — Number of entries   | 256   |
| — Circulating buffer  | Yes   |
| — retentive   | Yes   |
| — maintenance-free  | Yes   |

### Recipe management

|                                  |           |
|----------------------------------|-----------|
| • Number of recipes              | 50        |
| • Data records per recipe        | 100       |
| • Entries per data record        | 100       |
| • Size of internal recipe memory | 256 kbyte |
| • Recipe memory expandable       | No        |


### Variables

|                                  |     |
|----------------------------------|-----|
| • Number of variables per device | 800 |
| • Number of variables per screen | 100 |
| • Limit values                   | Yes |
| • Multiplexing                   | Yes |
| • Structures                     | No  |
| • Arrays                         | Yes |

### Images

|                                 |     |
|---------------------------------|-----|
| • Number of configurable images | 250 |
| • Permanent window/default      | Yes |
| • Global image                  | Yes |
| • Pop-up images                 | No  |
| • Slide-in images               | No  |

|  |   |
|--|---|
| • Image selection by PLC               | Yes   |
| • Image number in the PLC              | Yes   |
| <b>Image objects</b>                   |   |
| • Number of objects per image          | 100   |
| • Text fields                          | Yes   |
| • I/O fields                           | Yes   |
| • Graphic I/O fields (graphics list)   | Yes   |
| • Symbolic I/O fields (text list)      | Yes   |
| • Date/time fields                     | Yes   |
| • Switches                             | Yes   |
| • Buttons                              | Yes   |
| • Graphic display                      | Yes   |
| • Icons                                | Yes   |
| • Geometric objects                    | Yes   |
| <b>Complex image objects</b>           |   |
| • Number of complex objects per screen | 10  |
| • Alarm view                           | Yes   |
| • Trend view                           | Yes   |
| • User view                            | Yes   |
| • Status/control                       | No  |
| • Sm@rtClient view                     | No  |
| • Recipe view                          | Yes   |
| • f(x) trend view                      | No  |
| • System diagnostics view              | Yes; System message buffer of the SIMATIC S7-1200 and S7-1500 |
| • Media Player                         | No  |
| • HTML browser                         | Yes   |
| • PDF display                          | No  |
| • IP camera display                    | No  |
| • Bar graphs                           | Yes   |
| • Sliders                              | No  |
| • Pointer instruments                  | No  |
| • Analog/digital clock                 | No  |
| <b>Lists</b>                           |   |
| • Number of text lists per project     | 300   |
| • Number of entries per text list      | 100   |
| • Number of graphics lists per project | 100   |
| • Number of entries per graphics list  | 100   |
| <b>Archiving</b>                       |   |
| • Number of archives per device        | 2; One message and one process value archive                  |
| • Number of entries per archive        | 10 000  |
| • Message archive                      | Yes   |
| • Process value archive                | Yes   |
| • Archiving methods                    |   |
| — Sequential archive                   | Yes   |
| — Short-term archive                   | Yes   |
| • Memory location                      |   |
| — Memory card                          | No  |
| — USB memory                           | Yes   |
| — Ethernet                             | No  |
| • Data storage format                  |   |
| — CSV                                  | No  |
| — TXT                                  | Yes   |
| — RDB                                  | No  |
| <b>Security</b>                        |   |
| • Number of user groups                | 50  |
| • Number of user rights                | 32  |
| • Number of users                      | 50  |
| • Password export/import               | Yes   |
| • SIMATIC Logon                        | No  |
| <b>Character sets</b>                  |   |
| • Keyboard fonts                       |   |

|  |   |
|--|---|
| — US English   | Yes   |
| <b>Transfer (upload/download)</b>                      |   |
| • MPI/PROFIBUS DP                                      | No  |
| • USB  | No  |
| • Ethernet   | Yes   |
| • using external storage medium                        | Yes   |
| <b>Process coupling</b>                                |   |
| • S7-1200  | Yes   |
| • S7-1500  | Yes   |
| • S7-200   | Yes   |
| • S7-300/400   | Yes   |
| • LOGO!  | Yes   |
| • WinAC  | Yes   |
| • SINUMERIK  | Yes; No access to NCK data  |
| • SIMOTION   | Yes   |
| • Allen Bradley (EtherNet/IP)                          | Yes   |
| • Allen Bradley (DF1)                                  | No  |
| • Mitsubishi (MC TCP/IP)                               | Yes   |
| • Mitsubishi (FX)                                      | No  |
| • OMRON (FINS TCP)                                     | No  |
| • OMRON (LINK/Multilink)                               | No  |
| • Modicon (Modbus TCP/IP)                              | Yes   |
| • Modicon (Modbus)                                     | No  |
| <b>Service tools/configuration aids</b>                |   |
| • Backup/Restore manually                              | Yes   |
| • Backup/Restore automatically                         | No  |
| • Simulation   | Yes   |
| • Device switchover                                    | Yes   |
| <b>Peripherals/Options</b>                             |   |
| Printer  | No  |
| SIMATIC HMI MM memory card: Multi Media Card           | No  |
| SIMATIC HMI SD memory card: Secure Digital memory card | No  |
| SIMATIC HMI CF memory card Compact Flash Card          | No  |
| USB memory   | Yes   |
| SIMATIC IPC USB Flashdrive (USB stick)                 | Yes   |
| SIMATIC HMI USB stick                                  | Yes   |
| <b>Mechanics/material</b>                              |   |
| Enclosure material (front)                             |   |
| • Plastic  | Yes   |
| • Aluminum   | No  |
| • Stainless steel                                      | No  |
| <b>Dimensions</b>                                      |   |
| Width of the housing front                             | 214 mm  |
| Height of housing front                                | 158 mm  |
| Mounting cutout, width                                 | 198 mm  |
| Mounting cutout, height                                | 142 mm  |
| Overall depth  | 39 mm   |
| <b>Weights</b>   |   |
| Weight (without packaging)                             | 780 g   |
| Weight (with packaging)                                | 990 g   |
| <b>last modified:</b>                                  | 3/12/2024  |