

Siemens
EcoTech




SIMATIC S7-1500, digital input module DI 32x24 V DC HF, 32 channels in groups of 16; of which 2 inputs as counters can be used; input delay 0.05..20 ms input type 3 (IEC 61131); diagnostics; hardware interrupts: front connector (screw terminals or push-in) to be ordered separately



Figure similar

| General information | |
|--|--|
| Product type designation | DI 32x24VDC HF |
| HW functional status | from FS04 |
| Firmware version | V2.2.1 |
| <ul style="list-style-type: none"> FW update possible | Yes |
| Product function | |
| <ul style="list-style-type: none"> I&M data | Yes; I&M0 to I&M3 |
| <ul style="list-style-type: none"> Isochronous mode | Yes |
| <ul style="list-style-type: none"> Prioritized startup | Yes |
| Engineering with | |
| <ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated from version | V13 SP1 / - |
| <ul style="list-style-type: none"> STEP 7 configurable/integrated from version | V5.5 SP3 / - |
| <ul style="list-style-type: none"> PROFIBUS from GSD version/GSD revision | V1.0 / V5.1 |
| <ul style="list-style-type: none"> PROFINET from GSD version/GSD revision | V2.3 / - |
| Operating mode | |
| <ul style="list-style-type: none"> DI | Yes |
| <ul style="list-style-type: none"> Counter | Yes |
| <ul style="list-style-type: none"> Oversampling | No |
| <ul style="list-style-type: none"> MSI | Yes |
| Supply voltage | |
| Rated value (DC) | 24 V |
| permissible range, lower limit (DC) | 19.2 V |
| permissible range, upper limit (DC) | 28.8 V |
| Reverse polarity protection | Yes |
| Input current | |
| Current consumption, max. | 40 mA; 20 mA per group with 24 V DC supply |
| Power | |
| Power available from the backplane bus | 1.1 W |
| Power loss | |
| Power loss, typ. | 4.2 W |
| Digital inputs | |
| Number of digital inputs | 32 |
| Digital inputs, parameterizable | Yes |
| Source/sink input | P-reading |
| Input characteristic curve in accordance with IEC 61131, type 3 | Yes |
| Digital input functions, parameterizable | |

| | |
|--|--|
| • Gate start/stop | Yes |
| • Freely usable digital input | Yes |
| • Counter | |
| — Number, max. | 2 |
| — Counting frequency, max. | 6 kHz; FS04 and FW V2.2.1 or higher |
| — Counting width | 32 bit |
| — Counting direction up/down | Up |
| Input voltage | |
| • Rated value (DC) | 24 V |
| • for signal "0" | -30 to +5 V |
| • for signal "1" | +11 to +30V |
| Input current | |
| • for signal "1", typ. | 2.5 mA |
| Input delay (for rated value of input voltage) | |
| for standard inputs | |
| — parameterizable | Yes; 0.05 / 0.1 / 0.4 / 1.6 / 3.2 / 12.8 / 20 ms |
| — at "0" to "1", min. | 0.05 ms |
| — at "0" to "1", max. | 20 ms |
| — at "1" to "0", min. | 0.05 ms |
| — at "1" to "0", max. | 20 ms |
| for interrupt inputs | |
| — parameterizable | Yes |
| for technological functions | |
| — parameterizable | Yes |
| Cable length | |
| • shielded, max. | 1 000 m |
| • unshielded, max. | 600 m |
| Encoder | |
| Connectable encoders | |
| • 2-wire sensor | Yes |
| — permissible quiescent current (2-wire sensor), max. | 1.5 mA |
| Isochronous mode | |
| Filtering and processing time (TCI), min. | 80 µs; At 50 µs filter time |
| Bus cycle time (TDP), min. | 250 µs |
| Interrupts/diagnostics/status information | |
| Diagnostics function | Yes |
| Alarms | |
| • Diagnostic alarm | Yes |
| • Hardware interrupt | Yes |
| Diagnoses | |
| • Monitoring the supply voltage | Yes |
| • Wire-break | Yes; to I < 350 µA |
| • Short-circuit | No |
| Diagnostics indication LED | |
| • RUN LED | Yes; green LED |
| • ERROR LED | Yes; red LED |
| • Monitoring of the supply voltage (PWR-LED) | Yes; green LED |
| • Channel status display | Yes; green LED |
| • for channel diagnostics | Yes; red LED |
| • for module diagnostics | Yes; red LED |
| Potential separation | |
| Potential separation channels | |
| • between the channels | Yes |
| • between the channels, in groups of | 16 |
| • between the channels and backplane bus | Yes |
| • between the channels and the power supply of the electronics | No |
| Isolation | |
| Isolation tested with | 707 V DC (type test) |
| Standards, approvals, certificates | |
| Suitable for safety functions | No |

| Ecological footprint | |
|--|---|
| • environmental product declaration | Yes |
| Global warming potential | |
| — global warming potential, (total) [CO2 eq] | 18.9 kg |
| — global warming potential, (during production) [CO2 eq] | 12.1 kg |
| — global warming potential, (during operation) [CO2 eq] | 7.66 kg |
| — global warming potential, (after end of life cycle) [CO2 eq] | -1.02 kg |
| product functions / security / header | |
| signed firmware update | No |
| data integrity | No |
| Ambient conditions | |
| Ambient temperature during operation | |
| • horizontal installation, min. | -30 °C; From FS05 |
| • horizontal installation, max. | 60 °C |
| • vertical installation, min. | -30 °C; From FS05 |
| • vertical installation, max. | 40 °C |
| Altitude during operation relating to sea level | |
| • Installation altitude above sea level, max. | 5 000 m; Restrictions for installation altitudes > 2 000 m, see manual |
| Dimensions | |
| Width | 35 mm |
| Height | 147 mm |
| Depth | 129 mm |
| Weights | |
| Weight, approx. | 260 g |
| last modified: | 10/9/2024  |