



QS30LPQ-800438

▶ PRODUCTS FOR INDUSTRIAL AUTOMATION



WORLD-BEAM QS30 Series: Polarized Retro

Range: 8 m; Input: 10-30 V dc

Output: Complementary PNP

Euro-Style Quick-Disconnect

Part Number: 800438

CERTIFICATIONS



SPECIFICATIONS

Sensing Mode (General)	Retroreflective
Housing Style	Rectangular w/M30 Mount
Max Sensing Range (mm)	8000
Outputs	PNP
Power Supply/Supply Voltage	10-30 V dc
Connection	2 m Cable
Quick Disconnect Type	No QD
Sensing Beam	Visible Red LED
Operation	Light/Dark Operate
Max Op. Temp. (°C)	70
Min Op. Temp. (°C)	-20

Output response time (ms)	2
Special Feature: Intrinsically Safe	No
Special Feature: Remote Teach	No
Special Feature: Water Detection	No
IP Rating	IP67
Delay at Power-up (ms)	100
Repeatability (μs)	500
Number of Pins	5
NEMA Rating	NEMA 6
Max Op. Relative Humidity [%]	95% @ 55°C
Lens Material	Acrylic
Adjustments	Potentiometer
Barrel Diameter (mm)	30
Indicator	LEDs
Opposed Mode Emitter/Receiver	N/A



Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America